



## MaiA DS3 Stereo Integrated Amp

A compact, high-fidelity amp/receiver for up to 9 analog & digital audio sources.

Color options:  

- Powerful 140 watts per channel at 4 ohms
- PCM 1795DB 32bit/192kHz Delta-Sigma DAC
- BT 5.0 receiver with aptX, aptX HD, A2DP profile
- 9 total analog & digital inputs
- Sub & variable output
- Built-in MM/MC phono stage
- Dual-mono design
- XMOS asynchronous USB (24bit/192kHz)
- DSD capability (DSD64, DSD128; DSD256)
- Headphone output : 2x 430mW, 32ohm (1%THD)
- Trigger in & out
- Aluminum chassis protects against interference
- Remote control included
- Available in silver or black
- Magnetic wooden side panes sold separately
- Gold-plated ins/outs
- Made in Europe

**Power output:** 2x 80W/140W at 8 ohms/4 ohms (1%THD)  
**Frequency response (20Hz-20kHz):** < +/- 0.3dB @ 20kHz  
**SNR:** 97dB @ 1kHz (105dB 'A' weighted)  
**THD:** < 0.01% at 10W / 8 ohms  
**Headphone amp output:** 2x 430mW at 32 ohms (1%THD)  
**Line level inputs:** 3 pair RCA (sensitivity: 860mV)  
**Phono input:** 1 pair RCA (for MM, MI and MC cartridges)  
**Phono input sensitivity:** MM = 47k ohms / MC = 100 ohms  
**Phono input gain:** MM = 40dB / MC = 60dB  
**USB input:** USB Audio Class 2 (requires USB 2.0 or higher)  
**PCM sample rates:** up to 192kHz/24bit  
**DSD support:** DSD64, DSD128, DSD256  
**BT version & codec:** BT 5.0; aptX, aptX HD, A2DP profile  
**Trigger in/out:** 12V on/off detector  
**Outboard power supply:** 36V/5.5A DC  
**Power consumption:** <0.5W standby  
**Dimensions (WxHxD):** 8.11 x 2.8 x 9.45" (9.92" with sockets)  
**Weight:** 4.08 lbs without power supply